

Compressed expanded graphite energy storage

Do compressed expanded natural graphite matrices affect PCM saturation and thermal conductivity?

Of these materials, compressed expanded natural graphite (CENG) matrices have received the most attention. Despite this attention, the effect that CENG processing has on PCM saturation and overall matrix thermal conductivity has not been fully investigated.

How is expanded graphite obtained?

The expandable graphite was then expanded by means of microwave irradiation to obtain expanded graphite (EG). Tetradecanol (TD)/EG composite form-stable phase change materials (PCMs) were prepared by mixing TD with EG through an autoclave method. The highest loading of TD in the composite form-stable PCMs with good form-stability was 93 wt. %.

How do you make expandable graphite?

Natural flake graphite was chemically intercalated to prepare expandable graphite. The expandable graphite was then expanded by means of microwave irradiation to obtain expanded graphite (EG). Tetradecanol (TD)/EG composite form-stable phase change materials (PCMs) were prepared by mixing TD with EG through an autoclave method.

Does graphite increase energy conversion capacity?

The energy conversion capacities (photo/electro-thermal conversion) increase as the expanded graphite mass fraction increases. The prepared composite PCM obviously overcomes the shortcomings of the pure polyethylene glycol, and highlights enormous application in the domains of multi-physical energy conversion and premium quality power absorption.

What is a form-stable erythritol/expanded graphite composite phase change material?

A form-stable erythritol/expanded graphite (EG) composite phase change material (PCM) for mid-temperature thermal energy storage (TES) was successfully developed by an "impregnation, compression and sintering" three-step method. Five composite samples were prepared with EG contents of 5, 8, 10, 12 and 15 wt%, respectively.

What is a hydrate salt/expanded graphite composite phase change material?

(American Chemical Society) A novel strategy for preparing hydrate salt/expanded graphite (EG) composite phase change materials (PCMs) with large latent heat capacity and high thermal conductivity is explored, which involves modifying EG with a surfactant, compressing the modified EG into a block, and immersing the block into a melted hydrate salt.

DOI: 10.1016/J.RENENE.2012.09.029 Corpus ID: 108839764; Heat transfer enhancement of neopentyl glycol using compressed expanded natural graphite for thermal energy storage @article{Wang2013HeatTE, title={Heat transfer enhancement of neopentyl glycol using compressed expanded natural graphite for thermal

energy storage }, author={Xianglei Wang ...

Heat transfer enhancement of paraffin wax using graphite foam for thermal energy storage. Author links open overlay panel Yajuan Zhong a b, Quanguo Guo a, Sizhong Li a b, Jingli Shi a, Lang Liu a. Show more. Add to Mendeley. ... Heat transfer enhancement of paraffin wax using compressed expanded natural graphite for thermal energy storage ...

Neopentyl glycol (NPG) was saturated into the compressed expanded natural graphite (CENG) matrices with different densities in an attempt to increase the thermal performance of NPG for latent heat thermal energy storage (LHTES) application.

Journal Article: Surface-Modified Compressed Expanded Graphite for Increased Salt Hydrate Phase Change Material Thermal Conductivity and Stability ... Thermal energy storage (TES) will play an essential role in the push toward efficient, electrified buildings, and phase change materials (PCMs) offer a high potential to fill that need. ...

Surface-modified compressed expanded graphite for increased salt hydrate phase change material thermal conductivity and stability ... Comprehensive performance of composite phase change materials based on eutectic chloride with SiO₂ nanoparticles and expanded graphite for thermal energy storage system. Renewable Energy, 172 (2021), pp. ...

DOI: 10.1016/J.CARBON.2009.09.033 Corpus ID: 136832862; Heat transfer enhancement of paraffin wax using compressed expanded natural graphite for thermal energy storage @article{Zhong2010HeatTE, title={Heat transfer enhancement of paraffin wax using compressed expanded natural graphite for thermal energy storage }, author={Yajuan Zhong and Sizhong Li ...

Keywords: phase change materials, thermal energy storage, compressed expanded natural graphite, thermal conductivity enhancement, porous material sorptivity, composite matrix 1. Introduction Porous graphite matrices can be used for a variety of energy material applications [1-3]. Particularly, they are

Thermal energy storage (TES) using phase change materials (PCMs) is promising due to their ability to passively store heat, and high storage capacity per unit mass/volume/cost [[1], [2], [3]]. For low temperature TES applications, paraffin wax is a very popular PCM because of its large latent heat, relatively low volume change during phase ...

Neopentyl glycol (NPG) was saturated into the compressed expanded natural graphite (CENG) matrices with different densities in an attempt to increase the thermal performance of NPG for latent heat thermal energy storage (LHTES) application. NPG uniformly disperses in the porous network of the expanded graphite. Measured results indicated that ...

DOI: 10.1016/j.tsep.2020.100836 Corpus ID: 233546413; Thermal cycling aging of encapsulated phase change material - Compressed expanded natural graphite composite @article{Soto2021ThermalCA, title={Thermal cycling aging of encapsulated phase change material - Compressed expanded natural graphite composite}, author={J{^o}se Soto ...

Downloadable (with restrictions)! Neopentyl glycol (NPG) was saturated into the compressed expanded natural graphite (CENG) matrices with different densities in an attempt to increase the thermal performance of NPG for latent heat thermal energy storage (LHTES) application. NPG uniformly disperses in the porous network of the expanded graphite.

Compressed expanded natural graphite (CENG) matrices with different densities were used to increase the thermal property of paraffin wax. To predict the performance of the paraffin wax/CENG ...

One method is to impregnate PCMs into compressed expanded natural graphite (CENG) matrices, which can improve thermal conductivity by a factor of 100. CENG matrices have received particular interest due to their low cost, high porosity, small (nano/micro) pore size, high pore density, high thermal conductivity, and ability to be ...

Phase change materials (PCMs) are used in various thermal energy storage applications but are limited by their low thermal conductivity. One method to increase conductivity involves impregnating organic PCMs into highly porous conductive matrix materials. ... Of these materials, compressed expanded natural graphite (CENG) matrices have received ...

KW - compressed expanded natural graphite. KW - phase change composite. KW - phase change materials. KW - porous material composite. KW - thermal conductivity enhancement. KW - thermal energy storage. M3 - Presentation. T3 - Presented at the ASME International Mechanical Engineering Congress and Exposition (IMECE) 2020, 16-19 November 2020. ER -

Compressed Expanded Natural Graphite (CENG) impregnated with Phase Change Material (PCM) is an interesting material for latent heat storage application requiring a high heat transfer rate.

Web: <https://arcingenieroslaspalmas.es>